

CM-P30



Handles labels and receipts Our CMP-30II provides mobile printing options for receipts and labels up to 3 inches wide. The CMP-30II shares the same advanced Bluetooth and WiFi technology and tough construction of the smaller CMP-20II mobile printer. This ensures quick and easy printing, with drop-in paper loading and paper out indicators, simple feed paths to eliminate the risk of jamming, and an integral tear bar to cut paper to the required length. • High capacity 3-inch diameter media roll • Long life Lithium Ion batteries • Bluetooth 4.2 • 2.4 and 5.0 Ghz Wireless LAN

Rating: Not Rated Yet

[Ask a question about this product](#)

[Citizen](#)

Description

Key Benefits

- **Paper width:** Paper width 80 mm
- **Paper load:** Quick and easy media changing - drop-in paper loading
- **Printing Speed:**
 - High speed printing - up to 100 mm per second
- **Mobile-POS ready**
- **Powerful - High capacity batteries for a full day's operation (status indicated by LED)**
- **Robust:** Robust - exceeds IP42 and survives multiple drops of 1.2 metres
- **Integral tear bar to cut labels at the gap**
- **Energy:**
 - AC adapter as standard designed to recharge batteries on-board the printer or via an external optional charging station
 - Lithium Ion battery technology and easy-to-change power packs

Specifications

Print Speed (maximum)	<ul style="list-style-type: none">• 4 inches per second (100 mm/s)
Print Width (maximum)	72 mm
Media Width (min to max)	25 - 80 mm
Media Sensor	Paper end and reflective black mark
Roll Size (max), Core Size	Diameter 2.20 inches (56 mm)
Size (W x D x H) and Weight	<ul style="list-style-type: none">• 120 x 152 x 70 mm, 0.6 Kg
Emulations (Languages)	<ul style="list-style-type: none">• CPCL™ compatibility• ESC/POS™• Zebra® ZPL2®
Media type	Thermal receipt paper
Environmental rating, drop test	Exceeds IP42. Survives multiple drops of 1.5 metres
Battery type and capacity	Hard pack 7.4V 2600mAh
Print Sizes	<ul style="list-style-type: none">• 3-inch receipt
Input power	100V-240V AC, 50/60Hz
Output power	8.4 volts, 1200 mA
Resolution	<ul style="list-style-type: none">• 203 dpi
Main Interface	Dual Interface Serial (RS-232 /mini DIN connector), USB (mini B connector)
Optional interfaces	<ul style="list-style-type: none">• Bluetooth with Apple™ MFi compatibility• Bluetooth Class 2• Compact Wireless LAN• Bluetooth 4.2